

# Super L VI Series™

## LARGE FORMAT DIGITIZERS

The Super L VI is the next generation of the well-known Super L VI Series family of digitizers—digitizers that set the standard in large format digitizing.



Professionals in construction estimating, CAD, textiles and other fields will appreciate the added flexibility and improved performance of the Super L VI series. The Super L VI systems now include an integrated USB connection that allows the digitizer to be powered from the USB port of the computer. When the Super L VI is connected via the integrated RS-232 Serial connection, or with the QuikRuler, an optional power supply is required.

With a resolution of up to 2540 lines-per-inch and accuracy of 0.010", the Super L VI is ideal for your


most demanding work. Sharing a workstation with co-workers is easy too because each user can select the pointing device they find most appropriate



for their job. Super L VI allows you to select a corded or cordless transducer—whichever suites your preference and your project. In addition, the transducers are available in your choice of two different styles, offering you the chance to select the style that is most comfortable for your hand. Whether you choose the 4- or 16-button cursor or the stylus pen, you don't have to compromise comfort for performance!



Super L VI's improved driver set, provided on CD in a user-friendly interface, makes set-up even easier. Custom configurations, previously available through the tablet hardware, are now available through a software configuration program that supports emulations of popular industry formats, including CalComp 3400 and Summagrid.



## FEATURES

### Choice of pointing devices

- 16-button cursor, corded or cordless
- 4-button diamond cursor, corded or cordless
- Click tip pen, corded or cordless

### Compatibility

- GTCO Type 5/5A
- Summagraphics
- CalComp
- Ensures compatibility with virtually all software packages

### Accurate

- Patented sensing technology provides up to 1/2540" (1/100mm) resolution
- $\pm 0.01$ " (0.25mm) accuracy

### Easy to Use

- Integrated USB connection allows digitizer to be powered through USB port on connected computer
- Software configuration for RS-232 Serial connection can be quickly configured with GTCO CalComp's SuperSet™ Menu
- SuperSet™ allows users to quickly switch between applications

### Lightweight

- Lightest weight rigid tablet available today
- Provides quick and easy set-up

### Durable and Dependable

- State-of-the-art materials
- Durable, tough work surface
- Backed by a two-year warranty

**GTCO CalComp**  
PERIPHERALS

# Super L VI Series™

## LARGE FORMAT DIGITIZERS

<b>Platform Support</b>	PC
<b>Software Drivers</b>	Microsoft Windows 95, 98, ME, NT, 2000, XP, and Vista compatible
<b>Hardware Interface</b>	USB, RS-232 and QuikRuler Port (Requires optional Power Supply)
<b>Accuracy</b>	±0.010 in/0.25 mm
<b>Resolution</b>	Up to 2,540 lines-per-inch/100 lines-per-mm
<b>Proximity</b>	1.0 in/25.4 mm with corded transducers 0.4 in/10.16 mm with cordless transducers
<b>Baud Rate</b>	Up to 38,400
<b>Data Rate</b>	Up to 200 coordinate pairs per second
<b>Technology</b>	Electromagnetic
<b>Output Formats</b>	GTCO Type 5/5A, Summagraphics, CalComp
<b>Operating Modes</b>	Line, continuous, line increment and continuous increment
<b>Power Supply</b>	120 V/60 Hz, 220 V/50 Hz (required for RS-232 serial connection) No supply required for USB connection
<b>Power Requirements</b>	5 Volts, DC, 100 mA current draw (USB) 9 Volts, DC, 200 mA current draw (with Power Supply)
<b>Certification</b>	UL 1950, EN60950, FCC, VCCI, CE, EN55024, EN55022, Industry Canada
<b>Operating Temperature</b>	50 to 104°F/10 to 40°C
<b>Storage Temperature</b>	-40 to +158°F/-40 to +70°C
<b>Humidity Range</b>	0 to 95%, noncondensing
<b>Operating Altitude</b>	Up to 15,000 ft/4,600 m
<b>Storage Altitude</b>	Up to 50,000 ft/15,200 m
<b>Warranty</b>	Two-year warranty, extended warranty available USA only

### Tablet Options and Physical Dimensions

Model	Active Area	Footprint	Weight	Average Shipping Weight
SL6-2024	20 x 24 in/508 x 610 mm	29 x 34 in/737 x 864 mm	13 lb/5.9 kg	31 lb/14.1 kg
SL6-2436	24 x 36 in/610 x 914 mm	32.5 x 46 in/826 x 1168 mm	19 lb/8.6 kg	42 lb/19.1 kg
SL6-3036	30 x 36 in/763 x 914 mm	35.3 x 44.5 in/896 x 1130 mm	19 lb/8.6 kg	42 lb/19.1 kg
SL6-3648	36 x 48 in/914 x 1219 mm	44.5 x 60 in/1130 x 1524 mm	30 lb/13.6 kg	70 lb/31.8 kg
SL6-4460	44 x 60 in/1117 x 1524 mm	52.5 x 69 in/1333 x 1753 mm	40 lb/18.2 kg	80 lb/36.4 kg

### Distributed by:

Solution Technologies, Inc.  
Toll-free: 1-800-731-3038  
Web Site: [www.soltechs.com](http://www.soltechs.com)

Solution Technologies, Inc.  
Toll-free: 1-800-731-3038

### European Headquarters

GTCO CalComp GmbH  
Kreiller Strasse 24  
81673 Munich ■ Germany

Voice +49.89.370012.0 ■ Fax +49.89.370012.12



### Included With Your Purchase

- Super L VI tablet and controller
- Corded or cordless transducer (as specified at time of order)
- CD ROM with Software Drivers and Electronic Users Manual
- USB Cable

### Transducer Options

- 16-button cursor, corded or cordless
- 4-button cursor, corded or cordless
- Click tip stylus, corded or cordless
- Inking inserts for corded stylus

### Other Options

- Plan hold down
- Clear overlay
- QuikRuler III Measuring Module
- Universal mounting brackets
- Manual lift/manual tilt pedestal
- RS-232 Kit (Power Supply and I/O Cable)

## GTCO CalComp

PERIPHERALS

### Corporate/Sales Office

7125 Riverwood Drive ■ Columbia, MD 21046

Voice 410.381.6688 ■ Fax 410.290.9065

Toll Free USA, Canada 800.344.4723

E-mail [sales@gtcocalcomp.com](mailto:sales@gtcocalcomp.com)

[www.gtcocalcomp.com](http://www.gtcocalcomp.com)

Continuing research and development may result in specification or appearance changes at any time.

Super L VI is a registered trademark of GTCO CalComp Inc. All other product names are trademarks or registered trademarks of their respective owners.

Order No. SLVI-10/06 Printed in U.S.A.

©2006 GTCO CalComp Inc. All rights reserved.